

# GEOPAVER & DUROPAVE

## MANUFACTURING

The primary raw material used in the manufacture of GeoPavers and DuroPave Tiles is granulated, recycled rubber. Sorted by particle size and cleaned of all steel and fiber, these particles are mixed with binders and re-fused into stylish pavers and floor tiles. The pressure of the molding presses remains low so as to permit a permeable matrix to form within the bricks. Water will slowly seep through the bricks, making them ideal for use outside or in aisles and grooming areas. Water will not puddle on them. The textured, rubber surface provides the final element of safety.

The color of these elegant products is in the binder, which coats the black rubber granules. The binder is UV stabilized, but it will eventually fade. Surface coating applied at that time will refresh the color and appearance of the bricks and tiles, making them an excellent, long term investment.



## THE ULTIMATE IN DESIGN & PERFORMANCE

### DESIGN

GeoPavers use a traditional interlocking paving brick design to capture a richness of appearance that is the envy of all who walk into a barn whose aisles are paved with it. The DuroPave Tiles use the terrazzo style of Italy to fashion similarly impressive designs. Regardless of the style you choose, you will be impressed with the resilient feel of security when you walk on these materials. The sense of safety is enhanced by the sound-absorbing nature of the permeable matrix of the bricks and tiles. The surface textures and warm colors complete the effect and lend credence to the statement, "This place looks like a million bucks!" DuroPave can even be applied to walls for added protection for your horses, and the super-resilience of DuroPave Plus can be used effectively in foaling stalls and hospital clinics.



888-FOR-MATS • PO Box 21 • Ashland, OR 97520

(UK) 0800-027-7898  
Unit 3, Marsh Farm  
Bowling Alley, Crondall  
Surrey GU10 5RJ, United Kingdom  
Phone: 44-1252-851-551 • Fax: 44-1252-851-552



[www.groupsummit.com](http://www.groupsummit.com)

# GEOPAVER & DUROPAVE

## GEOPAVER



### GEOPAVER HI PROFILE

Size: 7 3/4" long x 6 1/4" wide (19.7cm x 15.9cm)  
 Thickness: 1 3/4" (43mm)  
 Weight: 8.5 lbs/sq. ft. (41.25 kg/m2)  
 Color: Terra Cotta, Forest Green, Slate Gray, Black  
 Packed: 307 sq. ft./pallet (28.5 m2/pallet)

### GEOPAVER LOW PROFILE

Size: 7 3/4" long x 6 1/4" wide (19.7cm x 15.9cm)  
 Thickness: 7/8" (21.5mm)  
 Weight: 4.25 lbs/sq. ft. (20.6 kg/m2)  
 Color: Terra Cotta, Forest Green, Black  
 Packed: 614 sq. ft./pallet (57 m2/pallet)

## BEVELED EDGE RAMP



### GEOPAVER BEVELED EDGE RAMP (HI PROFILE)

Size: 39.4" x 12" (1m x 30.5cm)  
 Thickness: 1 3/4" (43mm)  
 Weight: 14 lbs (6.3 kg)  
 Color: Terra Cotta, Forest Green, Slate Gray, Black

### GEOPAVER BEVELED EDGE RAMP (LOW PROFILE)

Size: 39.4" x 12" (1m x 30.5cm)  
 Thickness: 7/8" (21.5mm)  
 Weight: 1.6 lbs (.72 kg)  
 Color: Terra Cotta, Forest Green, Black

## DUROPAVE



Bottom Surface

### DUROPAVE TILES

Size: 2' x 2' (61cm x 61cm)  
 Thickness: 1" (25.5mm)  
 Weight: 16 lbs. (7.2 kg)  
 Color: Terra Cotta, Slate Gray, Black

## BEVELED EDGE RAMP



### DUROPAVE BEVELED EDGE RAMP

Size: 48" x 4" (122cm x 10.1cm)  
 Thickness: 1" (25.5mm)  
 Weight: 5 lbs (2.25 kg)  
 Color: Terra Cotta, Slate Gray, Black



Pattern Top



Brick Top

### DUROPAVE OPTIONS

Duropave can be special ordered with optional Brick Top or Pattern (tile) Top design for enhanced, traditional or contemporary looks.

DUROPAVE TILES may be "locked" together by a cleverly designed dowel that holds them in place until you're ready to move them.

